

# Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)



## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Identification of the substance/preparation

**Product name or Trade name :**

Sikafloor 161 (A)

**Use of the substance/preparation :** Chemical product for construction and industry

### Company/undertaking identification

**Manufacturer/Distributor :** Sika Limited  
Watchmead Welwyn Garden City  
Hertfordshire. AL7 1BQ  
United Kingdom

**Telephone no. :** 01707 394444

**Fax no. :** 01707 329129

**e-mail address of person responsible for this SDS :** EHS@uk.sika.com

**Emergency telephone number :** +44 (0)1707 363899 (available during office hours).

## 2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification :** Xi; R36/38  
R43  
N; R51/53

**Human health hazards :** Irritating to eyes and skin. May cause sensitisation by skin contact.

**Environmental hazards :** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Additional warning phrases :** Contains epoxy constituents. See information supplied by the manufacturer.

**See section 11 for more detailed information on health effects and symptoms.**

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Chemical family/ Characteristics :** Filled and modified epoxy resin

Ingredient name	CAS number	%	EC number	Classification
Reaction product: bisphenol A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6	35-50	500-033-5	Xi; R36/38 R43 N; R51/53
oxirane, mono[(C12-14-alkyloxy)methyl]derivs	68609-97-2	2.5-5	271-846-8	Xi; R36/38 R43 N; R51/53
reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	9003-36-5	2.5-5	500-006-8	Xi; R36/38 R43 N; R51/53
benzyl alcohol	100-51-6	1-3	202-859-9	Xn; R20/22
solvent naphtha (petroleum), light arom.	64742-95-6	<0.25	265-199-0	R10 Xn; R65 Xi; R37 R66, R67 N; R51/53

**Date of issue :** 26.11.2010.

**MSDS no. :** 121796

1/7

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

See section 16 for the full text of the R-phrases declared above

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

### 4. FIRST AID MEASURES

#### First-aid measures

- Inhalation** : Get medical attention if adverse health effects persist or are severe.
- Ingestion** : Do not induce vomiting unless directed to do so by medical personnel. Maintain an open airway. Seek immediate medical attention.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention if symptoms occur.
- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

See section 11 for more detailed information on health effects and symptoms.

### 5. FIRE-FIGHTING MEASURES

#### Extinguishing media

- Suitable** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
halogenated compounds  
metal oxide/oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

## 6. ACCIDENTAL RELEASE MEASURES

- Large spill** : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment.
- Small spill** : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment.

## 7. HANDLING AND STORAGE

- Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Avoid release to the environment. Refer to special instructions/safety data sheet. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous.
- Storage** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.
- Packaging materials**
- Recommended** : Use original container.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure limit values

<u>Ingredient name</u>	<u>Occupational exposure limits</u>
☒ No exposure limit value known.	

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

### Exposure controls

- Occupational exposure controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.
- Respiratory protection** : No special measures required.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Hand protection</b>	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: Butyl rubber/nitrile rubber gloves.
<b>Eye protection</b>	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
<b>Skin protection</b>	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.
<b>Environmental exposure controls</b>	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### General information

#### Appearance

<b>Form</b>	: Viscous mass.
<b>Colour</b>	: Grey.
<b>Odour</b>	: Faint odour.

#### Important health, safety and environmental information

<b>pH</b>	: 6
<b>Flash point</b>	: Closed cup: ~89°C (192.2°F)
<b>Density</b>	: ~1.6 g/cm <sup>3</sup> [20°C (68°F)]
<b>Solubility</b>	: Insoluble in the following materials: water

## 10. STABILITY AND REACTIVITY

<b>Stability</b>	: The product is stable.
<b>Conditions to avoid</b>	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Avoid release to the environment. Refer to special instructions/safety data sheet.
<b>Materials to avoid</b>	: Reactive or incompatible with the following materials: oxidizing materials
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 11. TOXICOLOGICAL INFORMATION

### Potential acute health effects

<b>Inhalation</b>	: May cause irritation.
<b>Ingestion</b>	: Irritating to mouth, throat and stomach.
<b>Skin contact</b>	: Irritating to skin. May cause sensitisation by skin contact.
<b>Eye contact</b>	: Irritating to eyes.
<b>Chronic effects</b>	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

## 12. ECOLOGICAL INFORMATION

**Environmental effects** : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 13. DISPOSAL CONSIDERATIONS

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

**European waste catalogue (EWC)** : 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances

**Packaging** : Completely emptied packaging or practically empty packaging containing dried/cured residues, once relieved of all pressure can be disposed of as non-hazardous waste.

Packaging may still contain hazardous residues and disposal should undertaken by a licensed waste contractor.

Any disposal practice must be in compliance with local and national laws and regulations.

15 01 10\* packaging containing residues of or contaminated by dangerous substances

## 14. TRANSPORT INFORMATION

### International transport regulations

#### ADR

**UN number** : UN3082  
**ADR Class** : 9  
**Classification code** : M6  
**Packing group** : III  
**Proper shipping name** : Environmentally hazardous substance, liquid, n.o.s.  
**Contains** : Epoxide resin  
**Label No.** : 9

#### IMDG

**UN number** : UN3082  
**IMDG Class** : 9  
**Packing group** : III  
**Proper shipping name** : Environmentally hazardous substance, liquid, n.o.s.  
**Contains** : Epoxide resin  
**Emergency schedules (EmS)** : F-A, S-F  
**Marine pollutant** : P  
**Label no.** : 9

#### IATA

**UN number** : UN3082  
**IATA Class** : 9  
**Packing group** : III  
**Proper shipping name** : Environmentally hazardous substance, liquid, n.o.s.

## 14. TRANSPORT INFORMATION

Contains : Epoxide resin  
Label no. : 9

## 15. REGULATORY INFORMATION

### EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

Hazard symbol or symbols : Xi, N  
Irritant, Dangerous for the environment

Contains : reaction product: bisphenol A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)  
oxirane, mono[(C12-14-alkyloxy)methyl]derivs  
reaction product: bisphenol F-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

Risk phrases : R36/38- Irritating to eyes and skin.  
R43- May cause sensitisation by skin contact.  
R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases : S24- Avoid contact with skin.  
S37- Wear suitable gloves.

Additional warning phrases : Contains epoxy constituents. See information supplied by the manufacturer.

VOC content (EU) :  VOC (w/w): 3.27%

### National regulations

Regulatory information : Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (CHIP 4)  
Control of Substances Hazardous to Health Regulations 2002 (COSHH) (as amended)  
Health & Safety at Work Act 1974  
The Environmental Protection (Duty of Care) Regulations 1991  
Hazardous waste regulations 2005  
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007

Guidance Publications : Approved Code of Practice - Management of Health and Safety at Work, HSE  
General Approved Code of Practice to COSHH Regulations, HSE.

## 16. OTHER INFORMATION

Full text of classifications referred to in sections 2 and 3 :  R10- Flammable.  
R20/22- Harmful by inhalation and if swallowed.  
R65- Harmful: may cause lung damage if swallowed.  
R37- Irritating to respiratory system.  
R36/38- Irritating to eyes and skin.  
R43- May cause sensitisation by skin contact.  
R66- Repeated exposure may cause skin dryness or cracking.  
R67- Vapours may cause drowsiness and dizziness.  
R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Full text of classifications referred to in sections 2 and 3 :  Xn - Harmful  
Xi - Irritant  
N - Dangerous for the environment

## 16. OTHER INFORMATION

### History

Date of printing : 26.11.2010.

Date of issue : 26.11.2010.

Date of previous issue : 08.09.2010.

☑ Indicates information that has changed from previously issued version.

### Notice to reader

*The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.*

# Safety Data Sheet

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - United Kingdom (UK)



## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Identification of the substance/preparation

**Product name or Trade name :**

Sikafloor®-161 (B)

**Use of the substance/preparation :** Chemical product for construction and industry

### Company/undertaking identification

**Manufacturer/Distributor :** Sika Limited  
Watchmead Welwyn Garden City  
Hertfordshire. AL7 1BQ  
United Kingdom

**Telephone no. :** 01707 394444

**Fax no. :** 01707 329129

**e-mail address of person responsible for this SDS :** EHS@uk.sika.com

**Emergency telephone number :** +44 (0)1707 363899 (available during office hours).

## 2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification :** Xn; R20/22  
C; R34  
R43  
N; R50/53

**Human health hazards :** Harmful by inhalation and if swallowed. Causes burns. May cause sensitisation by skin contact.

**Environmental hazards :** Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

See section 11 for more detailed information on health effects and symptoms.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Chemical family/ Characteristics :** Modified polyamine, containing solvent

Ingredient name	CAS number	%	EC number	Classification
benzyl alcohol	100-51-6	35-50	202-859-9	Xn; R20/22 [1]
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	10-25	220-666-8	Xn; R21/22 [1] C; R34 R43 R52/53
solvent naphtha (petroleum), light arom.	64742-95-6	5-10	265-199-0	R10 [1] Xn; R65 Xi; R37 R66, R67 N; R51/53
m-phenylenebis(methylamine)	1477-55-0	5-7	216-032-5	Xn; R20/22 [1] [2] C; R35 R43 R52/53
dodecylphenol, branched	121158-58-5	2.5-5	310-154-3	Repr. Cat. 3; R62 [1] C; R34

**Date of issue :** 08.09.2010.

**MSDS no. :** 121422

1/7



### 3. COMPOSITION/INFORMATION ON INGREDIENTS

2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	3-5	202-013-9	N; R50/53 Xn; R22 Xi; R36/38	[1]
See section 16 for the full text of the R-phrases declared above					

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] PBT-substance

[4] vPvB-substance

Occupational exposure limits, if available, are listed in section 8.

### 4. FIRST AID MEASURES

#### First-aid measures

- Inhalation** : Get medical attention immediately. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus.
- Ingestion** : Get medical attention immediately. Do not induce vomiting unless directed to do so by medical personnel. Chemical burns must be treated promptly by a physician. Maintain an open airway.
- Skin contact** : Get medical attention immediately. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Eye contact** : Get medical attention immediately. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

**Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

See section 11 for more detailed information on health effects and symptoms.

### 5. FIRE-FIGHTING MEASURES

#### Extinguishing media

- Suitable** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flames, smoking or flames in hazard area. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.
- Large spill** : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment.
- Small spill** : Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment.

## 7. HANDLING AND STORAGE

- Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Avoid release to the environment. Refer to special instructions/safety data sheet. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use non-sparking tools. Empty containers retain product residue and can be hazardous.
- Storage** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.
- Packaging materials**
- Recommended** : Use original container.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure limit values

<u>Ingredient name</u>	<u>Occupational exposure limits</u>
No exposure limit value known.	

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

### Exposure controls

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Occupational exposure controls</b>	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits.
<b>Hygiene measures</b>	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.
<b>Respiratory protection</b>	: No special measures required.
<b>Hand protection</b>	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: Butyl rubber/nitrile rubber gloves.
<b>Eye protection</b>	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
<b>Skin protection</b>	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Use barrier skin cream.
<b>Environmental exposure controls</b>	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### General information

#### Appearance

<b>Form</b>	: Liquid.
<b>Colour</b>	: Yellowish.
<b>Odour</b>	: Amine-like.

#### Important health, safety and environmental information

<b>pH</b>	: 11
<b>Flash point</b>	: Closed cup: ~68°C (154.4°F)
<b>Explosion limits</b>	: Lowest known value: Lower: 0.8% (solvent naphtha (petroleum), light arom.) Highest known value: Upper: 7% (solvent naphtha (petroleum), light arom.)
<b>Vapour pressure</b>	: Highest known value: 0.5 kPa (3.75 mm Hg) (solvent naphtha (petroleum), light arom.)
<b>Density</b>	: ~1 g/cm <sup>3</sup> [20°C (68°F)]
<b>Solubility</b>	: Insoluble in the following materials: water

## 10. STABILITY AND REACTIVITY

<b>Stability</b>	: The product is stable.
<b>Conditions to avoid</b>	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Avoid release to the environment. Refer to special instructions/safety data sheet.
<b>Materials to avoid</b>	: Reactive or incompatible with the following materials: oxidizing materials
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## 11. TOXICOLOGICAL INFORMATION

### Potential acute health effects

- Inhalation** : Harmful by inhalation. May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. May cause irritation.
- Ingestion** : Harmful if swallowed. May cause burns to mouth, throat and stomach.
- Skin contact** : Corrosive to the skin. Causes burns. May cause sensitisation by skin contact.
- Eye contact** : Corrosive to eyes. Causes burns.
- Chronic effects** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

## 12. ECOLOGICAL INFORMATION

- Environmental effects** : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Water polluting material. May be harmful to the environment if released in large quantities.

## 13. DISPOSAL CONSIDERATIONS

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.
- European waste catalogue (EWC)** : 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances
- Packaging** : Completely emptied packaging or practically empty packaging containing dried/cured residues, once relieved of all pressure can be disposed of as non-hazardous waste.
- Packaging may still contain hazardous residues and disposal should undertaken by a licensed waste contractor.
- Any disposal practice must be in compliance with local and national laws and regulations.
- 15 01 10\* packaging containing residues of or contaminated by dangerous substances

## 14. TRANSPORT INFORMATION

### International transport regulations

#### ADR

- UN number** : UN1760
- ADR Class** : 8
- Classification code** : C9
- Packing group** : III
- Proper shipping name** : Corrosive liquid, n.o.s.
- Contains** : Isophorondiamine, Solventnaphtha
- Label No.** : 8

#### IMDG

- UN number** : UN1760
- IMDG Class** : 8
- Packing group** : III

## 14. TRANSPORT INFORMATION

**Proper shipping name** : Corrosive liquid, n.o.s.  
**Contains** : Isophorondiamine, Solventnaphtha  
**Emergency schedules (EmS)** : F-A, S-B  
**Marine pollutant** : P  
**Label no.** : 8

### IATA

**UN number** : UN1760  
**IATA Class** : 8  
**Packing group** : III  
**Proper shipping name** : Corrosive liquid, n.o.s.  
**Contains** : Isophorondiamine, Solventnaphtha  
**Label no.** : 8

## 15. REGULATORY INFORMATION

### EU regulations

Classification and labeling have been determined according to EU Directives 67/548/EEC and 1999/45/EC (including amendments) and take into account the intended product use.

**Hazard symbol or symbols** : C, N  
 Corrosive, Dangerous for the environment  
**Contains** :  Benzyl alcohol  
 3-aminomethyl-3,5,5-trimethylcyclohexylamine  
 m-phenylenebis(methylamine)  
**Risk phrases** : R20/22- Harmful by inhalation and if swallowed.  
 R34- Causes burns.  
 R43- May cause sensitisation by skin contact.  
 R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
**Safety phrases** : S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
 S36/37/39- Wear suitable protective clothing, gloves and eye/face protection.  
 S45- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).  
**Restrictions on the Marketing and Use Directive** :  Restricted to professional users.  
**VOC content (EU)** : VOC (w/w): 48.17%

### National regulations

**Regulatory information** :  Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (CHIP 4)  
 Control of Substances Hazardous to Health Regulations 2002 (COSHH) (as amended)  
 Health & Safety at Work Act 1974  
 The Environmental Protection (Duty of Care) Regulations 1991  
 Hazardous waste regulations 2005  
 The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007  
**Guidance Publications** : Approved Code of Practice - Management of Health and Safety at Work, HSE  
 General Approved Code of Practice to COSHH Regulations, HSE.

## 16. OTHER INFORMATION

**Full text of classifications referred to in sections 2 and 3** : R10- Flammable.  
R62- Possible risk of impaired fertility.  
R22- Harmful if swallowed.  
R20/22- Harmful by inhalation and if swallowed.  
R21/22- Harmful in contact with skin and if swallowed.  
R65- Harmful: may cause lung damage if swallowed.  
R34- Causes burns.  
R35- Causes severe burns.  
R37- Irritating to respiratory system.  
R36/38- Irritating to eyes and skin.  
R43- May cause sensitisation by skin contact.  
R66- Repeated exposure may cause skin dryness or cracking.  
R67- Vapours may cause drowsiness and dizziness.  
R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Full text of classifications referred to in sections 2 and 3** : Repr. Cat. 3 - Toxic to reproduction category 3  
C - Corrosive  
Xn - Harmful  
Xi - Irritant  
N - Dangerous for the environment

### History

**Date of printing** : 08.09.2010.  
**Date of issue** : 08.09.2010.  
**Date of previous issue** : 03.06.2010.

☑ Indicates information that has changed from previously issued version.

### Notice to reader

*The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.*